TWIN M∧SK[™]

GPS IP68 Waterproof Parolee Tracker MT-200X

*AES128 Encryption *Waterproof IP68 *AGPS position assisted , WiFi /LBS position assisted when no GPS *SMS and GPRS (TCP/UDP) communication *Real time tracking * SOS button

*Data logger in no GSM signal area by flash (64M-bit) and send back data for compensation when GSM signal is back





*Vibration alarms includes : Exit Geofence Enter Geofence Near Geofence / Restricted area Unauthorized bracelet off / bracelet on Bracelet cut off Tampering by hitting No GPS signal No RF (No GPS + No WiFi signal) No GSM/ GPRS /3G signal Move out from specific route Over speed limit Low battery alarm

Bracelet drawing and dimensions

calibration mark 160mm 21mm 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 65 mm 187mm + 200mm 387mm

Items	Specification
EM size	70*64*22mm
Bracelet size	As attached
Net weight (include EM&	234g
bracelet& lock)	
Operating temperature	- 20 ~ +55C

GSM module	SIMCOM 5320E
	Support WCDMA900MHZ/WCDMA2100MHZ
GPS chipset	Ublox 7 chip
WIFI module	CDT-N582660-00
Position accuracy	<10M,2D RMS
Velocity accuracy	0.1M/S
Time accuracy	Satellite time : 1 microsecond time synchronization
Update time	Average 0.1 second
Hot start up	Average 3 second
Cold start up	Average 27 second
Max. altitude	18,000m (Max.60,000ft)
Max. speed	500m/s(Max. 1000 knots)
Max. acceleration	Less than 4g
Working time	Send data every 2 minute working >24 hours
Charging time	Upon low battery alarm at 20% , less then $<$ 2
	hours
Internal battery	4.2V, 1500mAH